


Transient Voltage Suppression Diodes Surface Mount – 6600W

Descriptions

Transient Voltage Suppressors (TVS) are semiconductor devices designed to provide protection against over voltage transients. When over voltage events occur, the silicon TVS activates from an very high impedance status to a very low impedance status by operating in the avalanche mode and uses a large junction area to absorb large transient currents in a fast response time, protecting voltage sensitive electronics equipment from damaging.

Boarden supplies unipolar and bipolar TVS devices with axial and SMD packages.



DO-218AB

Features

- Glass passivated chip junction in DO-218AB Package
- Junction passivation optimized design passivated anisotropic rectifier technology
- $T_J = 175^{\circ}\text{C}$ capability suitable for high reliability and automotive requirement
- Available in uni-directional polarity only
- Low leakage current
- Low forward voltage drop
- High surge capability
- Meets ISO7637-2 surge specification (varied by test condition)
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245°C
- AEC-Q101 qualified
- RoHS compliant

Applications

Used in sensitive electronics protection against voltage transients induced by inductive load switching and lighting, especially for automotive load dump protection application.

Maximum Ratings and Thermal Characteristics (TA=25°C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--|-----------------|--------------------------------------|----------------------|
| Peak Pulse Power Dissipation | P_{PPM} | with 10/1000 μs waveform | 6600 |
| | | with 10/10000 μs waveform | 5200 |
| Power dissipation on infinite heatsink at $T_C = 25^{\circ}\text{C}$ | P_D | 8.0 | W |
| Peak pulse current with 10/1000 μs waveform | $I_{PPM}^{(1)}$ | See next table | A |
| Peak Forward Surge Current, 8.3ms Single Half Sine-Wave | I_{FSM} | 700 | A |
| Operating junction and Storage Temperature Range | T_J, T_{STG} | -55~175 | $^{\circ}\text{C}$ |
| Typical Thermal Resistance Junction to Lead | $R_{\theta JC}$ | 0.9 | $^{\circ}\text{C/W}$ |

Notes:


1) Non-repetitive current pulse derated above $T_A = 25^{\circ}\text{C}$

Electrical Characteristics (TA=25°C unless otherwise noted)


| Part Number | | V _{RWM} | V _{BR@I_T} V | | I _T | I _{PP} | V _{C@I_{PP}Max.} | I _{R@V_{RWM}} | Package |
|-------------|----------|------------------|---------------------------------|-------|----------------|-----------------|-----------------------------------|--------------------------------|----------|
| UNT | BI | V | min. | max. | mA | A | V | uA | Package |
| SM8S10A | SM8S10A | 10.0 | 11.10 | 12.30 | 5 | 388.0 | 17.0 | 15 | DO-218AB |
| SM8S11A | SM8S11A | 11.0 | 12.20 | 13.50 | 5 | 363.0 | 18.2 | 10 | DO-218AB |
| SM8S12A | SM8S12A | 12.0 | 13.30 | 14.70 | 5 | 332.0 | 19.9 | 10 | DO-218AB |
| SM8S13A | SM8S13A | 13.0 | 14.40 | 15.90 | 5 | 307.0 | 21.5 | 10 | DO-218AB |
| SM8S14A | SM8S14CA | 14.0 | 15.60 | 17.20 | 5 | 284.0 | 23.2 | 10 | DO-218AB |
| SM8S15A | SM8S15CA | 15.0 | 16.70 | 18.50 | 5 | 270.0 | 24.4 | 10 | DO-218AB |
| SM8S16A | SM8S16CA | 16.0 | 17.80 | 19.70 | 5 | 254.0 | 26.0 | 10 | DO-218AB |
| SM8S17A | SM8S17CA | 17.0 | 18.90 | 20.90 | 5 | 239.0 | 27.6 | 10 | DO-218AB |
| SM8S18A | SM8S18CA | 18.0 | 20.00 | 22.10 | 5 | 226.0 | 29.2 | 10 | DO-218AB |
| SM8S20A | SM8S20CA | 20.0 | 22.20 | 24.50 | 5 | 204.0 | 32.4 | 10 | DO-218AB |
| SM8S22A | SM8S22CA | 22.0 | 24.40 | 26.90 | 5 | 186.0 | 35.5 | 10 | DO-218AB |
| SM8S24A | SM8S24CA | 24.0 | 26.70 | 29.50 | 5 | 170.0 | 38.9 | 10 | DO-218AB |
| SM8S26A | SM8S26CA | 26.0 | 28.90 | 31.90 | 5 | 157.0 | 42.1 | 10 | DO-218AB |
| SM8S28A | SM8S28CA | 28.0 | 31.10 | 34.40 | 5 | 145.0 | 45.4 | 10 | DO-218AB |
| SM8S30A | SM8S30CA | 30.0 | 33.30 | 36.80 | 5 | 136.0 | 48.4 | 10 | DO-218AB |
| SM8S33A | SM8S33CA | 33.0 | 36.70 | 40.60 | 5 | 124.0 | 53.3 | 10 | DO-218AB |
| SM8S36A | SM8S36CA | 36.0 | 40.00 | 44.20 | 5 | 114.0 | 58.1 | 10 | DO-218AB |
| SM8S40A | SM8S40CA | 40.0 | 44.40 | 49.10 | 5 | 102.0 | 64.5 | 10 | DO-218AB |
| SM8S43A | SM8S43CA | 43.0 | 47.80 | 52.80 | 5 | 95.1 | 69.4 | 10 | DO-218AB |

For all types maximum V_F = 1.8 V at I_F = 100 A measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum

I-V Curve Characteristics



Uni-Directional TVS



Bi-Directional TVS

V_{RWM} - Reverse Stand-Off Voltage - Working Peak Reverse Voltage

V_{BR} - Breakdown Voltage - Maximum current that flows through the TVS at a specified test current (I_T)

I_T - Test Current - Test Current

V_C - Clamping Voltage - Peak voltage measured across the suppressor at a specified I_{ppm} (peak impulse current)


I_{PP} - Peak Pulse Current - Maximum Reverse Peak Pulse Current

P_{PP} - Peak Pulse Power Dissipation - Max power dissipation


I_R - Reverse Leakage Current - Current measured at V_{RWM}

V_F - Forward Voltage - Drop for Uni-directional





Ratings and Characteristic Curves (TA=25°C unless otherwise noted)



Pulse Waveform- 10/1000µs



Pulse Derating Curve

Ratings and Characteristic Curves (TA=25°C unless otherwise noted)

**Load Dump Power Characteristics
(10ms Exponential Waveform)**

Reverse Power Capability

Typical Transient Thermal Impedance

Typical Junction Capacitance
Product Dimensions

| Dimensions | Inches | | Millimeters | |
|------------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.185 | 0.204 | 4.70 | 5.20 |
| A1 | 0.016 | - | 0.40 | - |
| B | 0.374 | 0.413 | 9.50 | 10.50 |
| b | 0.327 | 0.342 | 8.30 | 8.70 |
| C | 0.020 | 0.028 | 0.50 | 0.70 |
| D | 0.094 | 0.137 | 2.40 | 3.50 |
| E | 0.524 | 0.539 | 13.30 | 13.70 |
| E1 | 0.592 | 0.628 | 15.00 | 16.00 |
| e | 0.335 | 0.358 | 8.50 | 9.10 |
| e1 | 0.374 | 0.398 | 9.50 | 10.10 |
| L | 0.098 | 0.146 | 2.50 | 3.70 |
| L1 | 0.059 | 0.098 | 1.50 | 2.50 |

